# GH2 Source  Product Code

| GH2 Source | -XX | -XX | -XX | -XX | -XX | -XX | -XX | -XX |
|---|---|---|---|---|---|---|---|---|

**Flow Inlet:**

- **LI** = Left (FV – type plate)
- **RE** = Right (FV – type plate)

**Receipt printer with connection:**

- **A** = No receipt printer
- **B** = Incl. Receipt printer with connection

**ATEX-LED lamp:**

- **A** = No ATEX-LED lamp
- **B** = Incl. ATEX-LED lamp (for RS)

**Industrial connectors:**

- **B** = Industrial connector backside (for RS)
- **C** = Industrial connector with side-mounted input and output (for RS)
- **F** = Incl. 3.5 m cable with open end (not for RS)

**Helium leak test on the coriolis:**

- **A** = No ventilation grilles, no helium leak test
- **C** = Includes ventilation grilles, no helium leak test

**Maximum flow [kg/min]:**

- **4** = [Qmin=0.17 kg/min; Qmax= 4.17 kg/min]
- **20** = [Qmin=1 kg/min; Qmax= 20 kg/min]
- **21** = [Qmin=0.17 kg/min; Qmax= 20 kg/min]

**Model type:**

- **RK** = Without housing
- **RS** = With housing
- **DK** = With dual coriolis
- **TK** = With triple coriolis

**Maximum operating pressure:**

- **540** = Maximum operating pressure of 540 bar (RHM04/RHM10)
- **970** = Maximum operating pressure of 970 bar (RHM10)
- **1048** = Maximum operating pressure of 1048 bar (RHM04)

Examples of Product-Code:

**GH2 Source 540RS-20–A–C–B-A-RE**

TrigasDM GmbH • Erdinger Str. 2b • D - 85375 Neufahrn • www.trigasdm.com